







Straight from the jungle

If you are looking for an inspirting touch of green for your balcony, terrace or rooftop, you will like Mona Verdite Monobacking. Short piled so your furniture does not leave any marks, with a lively green that gives any space a bright and spring-like colour. Featuring our unique Verdite Monobacking!

STANDARD ROLLS

Pile out

2×25 m - 4×25 m

WARRANTY (Years - KLy)

5 - 600 KLy*

TESTS AND CERTIFICATES

DURABILITY_

- ISO 9001_QUALITY MANAGEMENT
- Colour fastness ≥ 4
- Water permeability 60l/min/m²

ENVIRONMENT_

• ISO 14001_ENVIRONMENTAL MANAGEMENT

SAFETY_

- Fire certification: Efl
- ISO 45001_Occupational health and safety management systems
- Social Audit, 2-Pillar SMET

Technical characteristics

Yarn



Type: Monofilament + Texturized

 Composition:
 60% PE - 40%PP

 Dtex.:
 7400 DTex (±5%)

 Pile weight:
 755 gr/m² (±10%)

 Colors:
 Monofilament: Drag

Monofilament: Dragon Texturized: Cream / Green

Tufting

Gauge: 3/8"
Pile height: 18 mm (±5%)
Total height: 20 mm (±5%)

Stitches: 230 lm (±10%) - 24150 m² (±10%)

Backing construction

Primary backing: Single Backing

100% pp, uv Stabilized

Finishing: Verdite Monobacking

DAG.410.MAR.15 / 2 / 1-9-24

REMARKS

In case infill is added to the Turfgrass artificial grass, please use rounded (non-angular), sieved, washed and dried silica sand. The use of any other type of infill material will invalidate the Turfgrass warranty.

*The standard warranties are applicable for regions with Global horizontal irradiation lower than or equal to 1800 KWH/m2/year or 155 KLy/m2/year. For regions with Global Horizontal Irradiation more than 1800 KWH/m2/year or 155 KLy/m2/year, please refer to our warranty statement.



Final product

Total weight: 1305 gr/m² (±10%)





In order to constantly improve the quality of our products to the latest technical standards, Turfgrass® reserves the right to modify any of the technical characteristics. The stated values are approximate average values and may vary by $\pm 10\%$ (fibre height $\pm 5\%$) due to technical reasons.

