



# GLUEDOWN TECHNICAL DATASHEET



Board: 1250 x 178 mm – Box: 15 boards (= 3,338 m<sup>2</sup>) – Pallet: 56 boxes (= 186,928 m<sup>2</sup>)  
 Board XXL: 1950 x 216 mm – Box: 9 boards (= 3,791 m<sup>2</sup>) – Pallet: 48 boxes (= 181,968 m<sup>2</sup>)  
 Tile: 650 x 650 mm – Box: 9 tiles (= 3,803 m<sup>2</sup>) – Pallet: 44 boxes (= 167,332 m<sup>2</sup>)  
 Tile: 650 x 325 mm – Box: 18 tiles (= 3,803 m<sup>2</sup>) – Pallet: 44 boxes (= 167,332 m<sup>2</sup>)

EN		GLUE 55
PRODUCT SPECIFICATION		
Total thickness	EN ISO 24346	2,30 mm
Wear layer	EN ISO 24340	0,55 mm
Total weight	EN ISO 23997	3,04 kg / m <sup>2</sup>
Surface treatment		PUR
Usage classification	EN ISO 10874	23 - 33 - 42
TEST RESULTS		
Underfloor heating	EN ISO 12524	Suitable max. 27°C (80°F)
Castor chair	EN ISO 4918	Pass
Fire resistance	EN ISO 13501-1	Bfl - s1
Chemical resistance	EN ISO 26987	OK
Residual indentation	EN ISO 24343-1	< 0,10 mm
Sound reduction: Impact Sound	EN ISO 717-2 (Δ Lw)	6 dB
Reflected Walking Sound	EPLF draft 021029-5 F1	** 16 sone (reduction of 79%)
Slip resistance	DIN 51130 EN ISO 13983	R11 Class DS
Light fastness	EN ISO 105-B02	> 6
Antistatic	EN ISO 1815	Yes
Residential warranty		Lifetime
Commercial warranty		10 years
U-Label		DIBt approval no. Z-156.603-1670



Made in Europe



# GLUEDOWN



- 1 Protective PU lacquer
- 2 Wear layer (0,55 mm)
- 3 Acoustic vinyl decor layer with fiberglass
- 4 Backing layer with fiberglass